Institute For Stem Cell Biology and Regenerative Medicine

Autonomous institute of the Department of Biotechnology, Government Of India



Ref: INS/L-5985/2019-2020(Y)

Date: 29/01/2020

ENQUIRY

Dear Sirs.

Please let us have your lowest Quotation for the following:

SI.No	Cat.No	Item Description	Make/Model	Item Qty	UOM
1		Electrical items as per the list Attached		1.00	No
				`	

Remarks:

Note:

1.	The	bids	shall	be	enclosed	in	an	envelope	,	and	due	date	sealed	duly	marked	"Tender	for
					ef No :											sed and t	
								e bids are l									
to	"THE	HEA	D-PU	RCI	HASE" w	ith T	end	er Ref No	an	d Iten	n Desc	criptio	n and di	ue date	e. The bid	s delivere	ed in
per	son sl	hall be	e dropp	ed i	in Purchas	e Se	ectio	n. If the b	ids	are s	sent th	irough	courier	or ma	ail, it sh	ould reach	h by
sul	omissi	on Da	te and	Time	e and inSte	m v	vill n	ot be respond	ons	ible f	or the	delay.					

2. DUE DATE FOR SUBMISSION OF QUOTATION AGAINST THIS ENQUIRY IS 14/02/2020 till 14.00 p.m.

- 3. QUOTATIONS RECEIVED AFTER THE DUE DATE SHALL BE REJECTED.
- 4. The Validity of your quotation should be for 60 days from the date.
- 5.All duties,taxes, surcharge and cess as currently applicable must be sated in your quotation, seperately. Otherwise your quote is liable to be rejected.
- 6. Your quotation should indicate delivery period & Warranty period.
- 7.Delivery to be made to our Stores. Please indicate charges, if any extra. Transit Insurance should be done upto inStem Stores.
- 8.If you are unable to supply the quality, specifications or brand as mentioned in our enquiry, Please state so and then offer alternative to quality/Specifications.
- 9.Payment :within one month after delivery & acceptance/satisfactory installation.
- 10.Please ensure that the enquiry number and the due date is superscribed on the envelope failing which your quotation is liable to be rejected.
- 11. Since we are a public funded research institution, we are exempted from paying Customs Duty(Except advolerum duty of 5% + 2% cess and CVD @4% vide Notification No.51/96 with latest amendments) and excise duty vide Notification No.10/97 CENTRAL EXCISE dated 01-03-1997 for all scientific equipments, technical instruments, equipments (including computers), their accessories, spares, consumables and software. Hence, please offer your prices taking this option into consideration.



Institute For Stem Cell Biology and Regenerative Medicine

Autonomous institute of the Department of Biotechnology, Government Of India



Ref: INS/L-5985/2019-2020(Y)

Date: 29/01/2020

12.If the item is covered under DGS&D rate contract, please quote the rate as per the DGS&D rate contract with xerox copy of the DGS&D order.

13. Any dispute or differences that may arise between the parties shall be referred to the sole arbitration of the Centre Director or his nominees. The decision of the arbitrator shall be final and binding on the parties. The venue for arbitration shall be Bangalore. The provisions of the Arbitration and Concillation Act, 1996 as amended from time to time shall apply. The Courts in Bangalore shall have exclusive jurisdiction to deal with any or all disputes between the parties.

Yours faithfully
For and on behalf of Insitute For Stem Cell
Biology and Regenerative Medicine

Yesu R

GKVK, Bellary Road, Bangalore-560065, INDIA

Phone No. : Email Id: 91-80-23666343/344/345/346 purchase@ncbs.res.in

Fax:

91-80-23636662

Website:

www.ncbs.res.in

If the items as per specifications in our P.O. is not supplied (shipped) within the specified delivery schedule, then liquidated damages (not in terms of penalty) will be imposed automatically and shall be deducted from the bill at the rate of 0.5% per week subject to a maximum of 10% of the order value.

NIC.	INS/L-5985/2019-2020(Y)		
L NO	ITEM DESCRIPTION	UNIT	QT
1	Heavy duty Gas filled power Capacitor for the following ratings		T
	Heavy duty Gas filled power Capacitor,5 KVAr,3 phase,Delta connection,dielectric:MPP 'SH',discharge resistor E,50		Т
a	Hz.Impregnant:NPCB,IE 60831:2002 .Ref:-LTCCN305B2 Make:L&T or Equivalent.	nos	
	Heavy duty Gas filled power Capacitor,10 KVAr,3 phase,Delta connection,dielectric:MPP 'SH',discharge resistor E,50		
b	Hz.Impregnant:NPCB,IE 60831:2002 .Ref:-LTCCN310B2 Make:L&Tor Equivalent.	nos	1
	Heavy duty Gas filled power Capacitor, 25 KVAr, 3 phase, Delta connection, dielectric: MPP 'SH', discharge resistor E, 50	\top	+
С	Hz,.Impregnant:NPCB,IE 60831:2002. Ref:-LTCCN325B2 Make:L&T or Equivalent.	nos	1
2	Capacitor Contactor for the following ratings		+
		+	\vdash
а	Capacitor duty contactor, for 5 KVAr capacitor, Coil voltage-500v, operating voltage 690v (Ref:-L&T MOC-8.5) or Equivalent.	nos	
		1	\vdash
b	Capacitor duty contactor, for 10 KVAr capacitor, Coil voltage-500v, operating voltage 1000v (Ref:-L&T MO C12.5) or Equivalent.	nos	1
			T
С	Capacitor duty contactor, for 25 KVAr capacitor, Coil voltage-500v, operating voltage 690v (Ref:-L&T MOC-25) or Equivalent.	nos	
			\vdash
d	Capacitor duty contactor, for 50 KVAr capacitor, Coil voltage-500v, operating voltage 1000v (Ref:-L&T MOC-50) or Equivalent.	nos	
	Add on block:Auxiliary Contactor add on block for left side, rated 415 voltage, 10A AC, 1NO, IEC 60947-5-1 Ref Make:-L&T MO-SA1L		T
е	or Equivalent.	nos	1
3	Pressure based liquid level sensor for the following ratings		┢
	Supply voltage:12-36V DC,Output:4-20mA,Range:0-5mH20,Measuring medium:Liquid,Material:Stainless steel.Make:Omicron		\vdash
а	sensor,10mtrs length,Model No:-L7521-7-005M or Equivalent.	nos	ı
	Supply voltage:12-36V DC,Output:4-20mA,Range:0-5mH20,Measuring medium:Liquid,Material:Stainless steel.Make:Omicron	 	\vdash
b	sensor,5mtrs length,Model No:-L7521-7-005M or Equivalent.	nos	ı
	LT CABLES:	-	\vdash
		-	\vdash
	Sheathed ,Stranded conductor, flat plate strip/wire armoured cables conforming to IS :7098/Part I (with latest amendments) and		
- 1	of follwing sizes. The cables shall bear ISI certification mark. Make: Finolex/Polycab or Equivalent.		
а	2C x10 sqmm xlpe aluminium cables		-
_	4C x 10 sqmm xlpe aluminium cables	mtr	1
-	4C x 16 sqmm xlpe aluminium cables	mtr	1
_	4C x 2.5 sqmm xlpe copper cables	mtr	1
	Cable Gland:-19mm Single Compression Brass Cable Glands	mtr	1
	Gland earthing clip:- Copper gland earthing clip required for the following armored cable brass compression gland	nos	_
3	for 19mm gland		_
	for 22mm gland	nos	
	for 25mm gland	nos	
	for 32mm gland	nos	
	for 38mm gland	nos	
-		nos	
	for 50mm gland	nos	
	Saddles:-Iron saddles confirming ISI standards for the following sizes		
-	20mm	nos	2
_	25mm	nos	20
_	32mm	nos	20
_	38mm	nos	10
_	50mm	nos	į
1	DC lamp with fitting:-12v 50w 36 degree,Diameter: 51 mm,Warm White,2950k lamp fitting		
5		nos	
i.a l	Halogen fitting:1x1000 w Halogen fitting with lamp 240v rated voltage	nos	
b	Halogen lamp suitable for the above 1000w fitting	nos	1
c l	Halogen fitting:1x500 w Halogen fitting with lamp 240v rated voltage	nos	
	Halogen lamp suitable for the above 500w fitting	nos	1
	ilica gel:-Silica Gel for transformer breather,color:-Blue	kg	_
	MCCB:MCCB 414/440v 50/60Hz for the following ratings	МБ	
	250A,3pole, Uipm:8kV,Icu:36kA,Ics:100%,CAT:A IEC 60947-2 Ref Make:-L&T DN2-250D,DN2 MTX 1.0	_	
ala	305 Japana, C. Jannary, 100. John, 103. 1007 June 100 347-2 Net 101 dke: -L&T DNZ-250D, DNZ MIX 1.0	nos	
a 2	preader links required for the above rated MCCR 2504.3 - 1 - 1.15 1.15	- 1	
S	preader links required for the above rated MCCB 250A 3 pole rated for both incoming side and outgoing side 6 pieces for each	set I	
b N	MCCB as per the ISI standards	set	
b N	MCCB as per the ISI standards DN delay timer:ON delay timer 5Amps@250V AC/28V DC Resistive Load with 2 NC & NO in it,Ref:-EAPL		
b N	MCCB as per the ISI standards ON delay timer:ON delay timer 5Amps@250V AC/28V DC Resistive Load with 2 NC & NO in it,Ref:-EAPL Model A1D1-X(60M) or Equivalent.	set nos	
b N 0 8 N 10 S	MCCB as per the ISI standards ON delay timer:ON delay timer 5Amps@250V AC/28V DC Resistive Load with 2 NC & NO in it,Ref:-EAPL Model A1D1-X(60M) or Equivalent. Supply of the following medium copper lugs		
b N 8 N 10 S a C	MCCB as per the ISI standards ON delay timer:ON delay timer 5Amps@250V AC/28V DC Resistive Load with 2 NC & NO in it,Ref:-EAPL Model A1D1-X(60M) or Equivalent. Supply of the following medium copper lugs		50



	c Copper reducer terminal-1.5sqmm		
	d Copper reducer terminal-2.5sqmm	nos	: 1
	e Copper reducer terminal-4sqmm	nos	1
	f Copper reducer terminal-6sqmm	nos	
	g Copper reducer terminal-10sqmm	nos	-
	h Copper reducer terminal-16sqmm	nos	_
	i Copper reducer terminal-25sqmm	nos	-
	j Copper reducer terminal-35sqmm	nos	-
_	Jeopper Teutre Congress take Association	nos	+
	k heavy duty Copper tube terminal-10sqmm with 8mm stud hole	_	+
_	I heavy duty Copper tube terminal-16sqmm with 8-10mm stud hole	nos	_
_	m heavy duty Copper tube terminal-25sqmm with 10mm stud hole	nos	\perp
	n heavy duty Copper tube terminal-35sqmm with 10mm stud hole	nos	+
	o Aluminium through lugs 16sqmm	nos	\perp
	p Aluminium through lugs 10sqmm	nos	_
_	q Aluminium through lugs 25sqmm	nos	\perp
	Copper reducer terminal-50sqmm	nos	
	s Copper tube terminal-50sqmm	nos	
1	1 POP screws for the following sizes	nos	T
	0.5"		T
	0.75"	nos	3
	1"	nos	10
	1.5"	nos	10
	2"	nos	2
	5 3"	nos	$\frac{1}{1}$
		nos	$\frac{1}{1}$
1	Cable tie for the following sizes	nos	1
	150mm		-
	200mm	pack	╀
	250mm	pack	-
3 a	Cable tie base 25x25mm of 100 nos each	pack	_
b	Cable tie base 20x20mm of 100 nos each	pack	
14	Wire multistranded single core copper FRLSH 90 mtrs coil for the following sizes	pack	
а	1 sqmm.(Grey-3,Black:-4)		
b	10sqmm(Red-1,yellow-1,blue-1,black-2,Green-2)	coil	
15	Hylam sheet:-Hylam sheet 1mtr by 1 mtr, 5mm thickness high quality	coil	
16	Timer :- Digital Timer TM-619-2 Make:Frontier or Equivalent.	nos	
7 a	Anchor fastner: 8mmx50mm Anchor fastner with hex nuts	nos	1
h	8mm nut: 8mm hex MS nuts	nos	15
	10mm washer for the 8mm bolt	kg	
	Torrin waster for the 8mm bolt	-	50
	Copper Material Busbar Pin Type 3 Pole Distribution Box Copper Connector Busbar ISO: 9001 Red copper and fire-resistant PVC for	1103	30
19			
_	32A	-	
	50A	nos	
С	63A	nos	
d	80A	nos	:
e	100A	nos	1
7	Copper Material Bushar Pin Type 2 Pole Distribution Pay Copper Service Devices	nos	1
20	Copper Material Busbar Pin Type 2 Pole Distribution Box Copper Connector Busbar ISO: 9001 Red copper and fire-resistant PVC for the following ratings of 100cm length		
_	20A		
_	32A	nos	2
-	50A	nos	
-	33A	nos	1
		nos	
,1	Copper Material Busbar Pin Type 1 Pole Distribution Box Copper Connector Busbar ISO: 9001 Red copper and fire-resistant PVC for	.103	1
1 t a 6	and the state of t		
		nos	3
3 [in rail: Steel Din rail 1mm thick 20-30mm width	pack	1
alī	erminal block/MCR pin rail-travial Plack/MCR pi	mtr	5
Ţ	Thinks blocky Web Din Fall. Terminal Block/ MCB Din Fall of 3-5 mm thick and 20-20 mm width	mtr	5
٠,	erminal block. Terminal Block required for the above digrail for 6A rating		100
	lug Top,Polycarbonate for the following ratings Make:Anchor or Equivalent	103	τOΩ
3 2	40V 6 AMP 3 PIN TOP		-
2	10 20 mm p 9 mm 10 p	nos	30
	outral links. Dec. No. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1.	nos	30
N	eutral link:Brass Neutral link with insulated base for the following sizes		



b	8way	nos	10
	10way	nos	10
	12way	nos	10
	Junction box Cover:Round PVC junction box closing cover	nos	50
	Earthing Strip:Flat earthing strip,Material Use :- M.S Flat,Size :- 25 x 6mm,Finishing :- Hot-Dip G.I , Electro Plating.	mtr	10
29	Wire Fastener Circle Cable Clip of hardened nail required for the following sizes of 100 nos	IIII	10
	6mm of diameter		 _
	8mm of diameter	pack	1 2
	10mm of diameter	pack	1
		pack	- 4
30	Flood light for the following rating conforming to IP65/66 standards		_
_	LED Flood light 20W,Input Voltage : AC220-240V, 50/60Hz	nos	4
	Operating voltage range: 90-305V,Flux:1700lm,6500K,220X50X311		
	Flood light 50W,Input Voltage: AC220-240V, 50/60HzOperating voltage range: 90-305V,Flux:5000lm,6500K,20x12x6 cm	nos	3
С	Flood light 100W,Input Voltage: AC220-240V, 50/60HzOperating voltage range: 90-305V,Flux:14000Im,6500K	nos	2
32	MS CONDUIT SHARP BEND:-Inspection sharp bend, SCREW TYPE, confirming to ISI standards, with ISI mark for the following sizes		
а	20mm to 20mm,1.6MM THICKNESS	nos	50
b	25mm to 25mm,1.6MM THICKNESS	nos	50
С	32mm to 32mm,1.6MM THICKNESS	nos	30
	MS CONDUIT ELBOWS:-Elbows	15	<u> </u>
	elbows, size 20mm to 20 mm, screw type, 1.6MM THICKNESS	nos	50
	elbows, size 25mm to 25 mm, screw type, 1.6MM THICKNESS		50
	Elbows ,size 32mm to 32 mm, screw type,1.6MM THICKNESS	nos	
	Saddles:-iron staples/ saddles/ screws confirming ISI standards for the following sizes	nos	30
	32 mm	nos	100
	20 mm	nos	200
	25 mm	nos	200
	MS perforated cable tray painted with powder coating 100 X 50 X 1.6 mm	mtr	30
36	CFL		
а	18W 2 pin CFL,Make:Philips	nos	25
b	18W 4 pin CFL, Make: Philips	nos	25
С	Electronic choke required for the above 18W 2pin lamp	nos	15
	14w t5 TUBELIGHT 2FEET,CFL	nos	10
37	LED lamp		
	18W LED PLL 4 Pin, Make:-Philips or Equivalent.	nos	30
	18W 4feet LED tube light, Make:-Philips or Equivalent.	-	25
	LED Driver for the following ratings	nos	25
			
d I	LED driver 9W,Input voltage:230V,Output Voltage:-30v,260mA,Make:-Philips or Equivalent.	nos	15
	LED driver 25W 700mA Output voltage:-28-39V,Input voltage:-240V Make:-Philips or Equivalent.	nos	5
	Supply of the following Wiring Accessories		
	6modular wrap around white front plate-MK or Equivalent.	nos	20
	6A SOCKET-MK-W26423	nos	100
d	6A SWITCH-MK-W26401A	nos	100
е	6A SOCKET-LEGRAND-ARTEOR-573470	nos	20
f	6A SWITCH-LEGRAND-ARTEOR-573400	nos	20
g	16A SOCKET-LEGRAND-ARTEOR-573471	nos	10
	20A SWITCH-LEGRAND-ARTEOR-573410	nos	10
-	3 modular-weather proof box-legrand-680613	nos	5
	6 MODULAR Legrand 054012 Matt Al Popup Box	NOS	5
	insulation tape make:Wonder Achem(Red=20,Yellow=20,Blue=20,Black=20,Green=20)	-	
	Cotton waste, cleaning cloth etc	NOS	100
		kg	5
	MPCB for the below ratings	+	
-	MPCB rotary 9-14A with 2NO 3pole ,Make:-Schneider Ref:-GV2ME16 or Equivalent.	nos	2
	MPCB Rotary 6.3-10.0,3pole,100kA with 2NO ,Make:-L&T Supernova Ref:-MOG-H1-1000 or Equivalent.	nos	1
С	MPCB rotary 4-6.3A,3pole,100kA with 2NO ,Make:-L&T supernova Ref:-MOG-HT-0630 or Equivalent.	nos	1
d	MPCB rotary 2.5-4A with 2NO ,Make:-L&T supernova Ref:-MOG-HT-0400 or Equivalent.	nos	1
42	Finned strip air heater double tube 1.5kW,230V rated around 12" length with base	nos	8
-	Gasoline Gauging Paste:Disel dipstick level indicating paste.	box	2
	Batteries:-Rocket 12V 18AH rechargeable Battery SMF VRLA (UPS Battery/Uninterrupted Power Supplies)	nos	10
	Rocket 12V 2.5AH rechargeable Battery SMF VRLA (UPS Battery/Uninterrupted Power Supplies)	nos	10
		IIIOS	TO

